

Appn. Number 10/705,840 Guyon et al.
Amendment dated Thursday, 04/13/2006
Reply to Office Action dated 01/24/2006
Amended 07/26/2006
Reply to Office Action dated 07/07/2006

RECEIVED
CENTRAL FAX CENTER

GAU 3618

JUL 26 2006

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended). An in line skate guard for an in line skate, said in line skate comprising a boot and a frame having a bottom surface and adapted for carrying a plurality of serially mounted rollers, said plurality of serially mounted rollers including a first roller and a last roller, wherein each of said plurality of rollers has a ~~first~~ width and a rounded rolling surface ~~a second circumferential arcuate taper~~ adapted for contacting a contact surface, and wherein the in line skate includes a brake spur, said in line skate guard comprising an elongate body comprising:
 - a. a length horizontal upper surface having a groove along the length thereof, said groove having a first width and a transitional bevel to a second width narrower than said first width wherein the groove is adapted for receiving and holding the plurality of serially mounted rollers in a pinching relationship thereby preventing their rotation;
 - b. a front portion having a first width, said front portion including opposite and parallel first and second lugs projecting upwards; a beveled bottom contacting surface comprising a plurality of contact planes for contacting a walking surface, wherein said elongate body is composed of:
 - c. a rear portion having a second width wider than said first width, said rear portion including opposite and parallel third and fourth lugs projecting upwards; and, a front portion having:

Appn. Number 10/705,840

Guyon et al.

GAU 3618

Amendment dated Thursday, 04/13/2006

Reply to Office Action dated 01/24/2006

Amended 07/26/2006

Reply to Office Action dated 07/07/2006

- i. a first width;
 - ii. opposite and parallel first and second lugs projecting upwards; and
 - iii. a front bottom surface adapted for purchase on said walking surface;
 - d. a middle portion contiguous with said front portion and having:
 - i. a third width equal to the first width[.];
 - ii. ~~the middle portion having~~ a groove comprising a groove first groove width,
and a transitional bevel to a groove second groove width[.]; and
 - iii. a middle bottom surface contiguous with said front bottom surface and
adapted for purchase on the contact walking surface; and
 - e. a rear portion having:
 - i. a second width wider than said first width;
 - ii. opposite and parallel third and fourth lugs projecting upwards; and
 - iii. a rear bottom surface contiguous with said middle bottom surface and
adapted for purchase on the walking surface.
- 2. (Currently Amended). The in line skate guard as claimed in claim 1 wherein: ~~said~~
~~elongate body further includes a bottom surface adapted for purchase on said contact~~
~~surface; said bottom surface comprising:~~
 - a. said front bottom surface comprises a first contact plane having an angle of
approximately 45 degrees to the contact surface; and, a second contact plane
having a slightly elevated angle above the contact surface wherein said second
contact plane equals approximately 20 percent of said beveled bottom contacting
surface;

Appn. Number 10/705,840

Guyon et al.

GAU 3618

Amendment dated Thursday, 04/13/2006

Reply to Office Action dated 01/24/2006

Amended 07/26/2006

Reply to Office Action dated 07/07/2006

- b. ~~a second contact plane having a slightly elevated angle above the contact surface;~~
said middle bottom contact surface comprises a third horizontal contact plane
wherein said third horizontal contact plane equals approximately 40 percent of the
beveled bottom contacting surface; and,
- c. ~~a third horizontal contact plane;~~ said rear bottom surface comprises a fourth contact
plane having a slightly elevated angle above the contact surface; and, a fifth contact
plane having an angle of approximately 45 degrees to the contact surface, wherein
said fourth contact plane equals approximately 20 percent of the beveled bottom
contacting surface. [;:]
- d. ~~a fourth contact plane having a slightly elevated angle above the contact surface,~~
~~and,~~
- e. ~~a fifth contact plane having an angle of approximately 45 degrees to the contact~~
~~surface.~~
3. (Currently Amended). The in line skate guard as claimed in claim 2 wherein said first
and second opposite and parallel lugs define a first front gap between them[.], and
wherein said first front gap is adapted to accept said width of said first roller.
4. (Original). The in line skate guard as claimed in claim 3 wherein said third and fourth
opposite and parallel lugs define a second rear gap said rear gap adapted in width to
receive said brake spur.
5. (Currently Amended). The in line skate guard as claimed in claim 4, ~~wherein the~~
~~elongate body has an upper surface and a groove within said upper surface, said groove~~

Appn. Number 10/705,840 Guyon et al.
Amendment dated Thursday, 04/13/2006
Reply to Office Action dated 01/24/2006
Amended 07/26/2006
Reply to Office Action dated 07/07/2006

GAU 3618

~~adapted to receive the plurality of serially mounted rollers in a pinching relationship,~~
wherein the groove is further defined by:

- a. a first wall having a top surface, an inside surface and an outside surface; and,
- b. a second wall having a top surface, an inside surface and an outside surface;

wherein said first wall and said second wall are adapted to flex outwards when the plurality of serially mounted rollers are inserted between them and in consequence hold the plurality of serially mounted rollers within the groove in a pinching relationship.

6. (Currently Amended). The in line skate guard as claimed in claim 5, wherein the groove further includes:

- a. a bottom surface adapted to engage the rounded rolling surface of each of the plurality of serially mounted rollers in a supporting relationship;
- b. wherein a the first groove first width is adapted to receive and hold said roller width in a pinching relationship ~~said first width of each of the plurality of serially mounted rollers; and;~~
- c. wherein said transitional bevel is adapted to receive and hold the rounded rolling surface of each of the plurality of serially mounted rollers in a pinching relationship. second groove width narrower than said first width; and,
- d. ~~a beveled portion transitioning between said first groove width and said second groove width said beveled portion adapted to receive in a pinching relationship said circumferential arcuate taper of each of the plurality of serially mounted rollers.~~

Appn. Number 10/705,840 Guyon et al.
Amendment dated Thursday, 04/13/2006
Reply to Office Action dated 01/24/2006
Amended 07/26/2006
Reply to Office Action dated 07/07/2006

GAU 3618

7. (Original). The in line skate guard as claimed in claim 6, wherein the groove further includes:
- a. a front curvilinear bight curving front wards and upwards into the first front gap to conform to the first roller;
 - b. a rear curvilinear bight curving rearwards and upwards into said rear gap to conform to the last roller; and,
 - c. a depth so that when the in line skate guard is fastened to the in line skate, the top surfaces of the first wall and the second walls respectively abut against the bottom surface of the frame.
8. (Original). The in line skate guard as claimed in claim 7 further comprising means for securing the elongate body to the plurality of serially mounted rollers, said means comprising:
- a. in the front portion:
 - i. a first aperture in the first lug;
 - ii. a second aperture in the second lug;wherein said first and second apertures include a countersunk portion on the inside walls of the first and second lugs respectively;
 - b. in the rear portion:
 - i. a third aperture in the third lug;
 - ii. a fourth aperture in the fourth lug;wherein said third and fourth aperture include a countersunk portion on the inside walls of the third and fourth lugs respectively;

Appn. Number 10/705,840

Guyon et al.

GAU 3618

Amendment dated Thursday, 04/13/2006

Reply to Office Action dated 01/24/2006

Amended 07/26/2006

Reply to Office Action dated 07/07/2006

- c. a first semi-circular pivot hoop having a first apex, said first semi circular pivot hoop mounted between the first lug and the second lug by first mounting means; and,
 - d. a second semi-circular pivot hoop having a second apex, said second semi circular pivot hoop mounted between the third lug and the fourth lug by second mounting means.
9. (Original). The in line skate guard as claimed in claim 8 wherein said semi circular first pivot hoop has a radius sufficient to permit said first apex to situate on top of the first roller.
10. (Original). The in line skate guard as claimed in claim 9 wherein said semi circular second pivot hoop has a radius sufficient to permit said second apex to situate on top of the in line skate brake spur, and where the in line skate brake spur is absent, said semi circular second pivot hoop has a radius sufficient to permit said second apex to situate on top of the in line skate last roller.
11. (Currently Amended). The in line skate as claimed in claim 10, wherein said first mounting means comprises a first and a second sleeve ~~inserted~~ disposed into the first lug aperture and second lug apertures respectively, wherein each of the first and second sleeves include a first end and a second end, said first and second sleeves' second end adapted in shape to conform to the countersunk portion of the first and second lug apertures, the first and second sleeve second ends slightly recessed in the first and second aperture inside end.

Appn. Number 10/705,840

Guyon et al.

GAU 3618

Amendment dated Thursday, 04/13/2006

Reply to Office Action dated 01/24/2006

Amended 07/26/2006

Reply to Office Action dated 07/07/2006

12. (Currently Amended). The in line skate as claimed in claim 11, said second mounting means comprises a third and a fourth sleeve ~~located~~ disposed within the rear portion third and fourth lug apertures respectively, wherein each of the third and fourth sleeves includes a first end and a second end wherein said third and fourth sleeves' second ends are adapted in shape to conform to the countersunk portion of the third and fourth lug apertures, the first and second sleeve ends of the third and fourth sleeves slightly recessed in the aperture inside end.
13. (Currently Amended). The in line skate guard as claimed in claim 12, wherein said means for securing the elongate body to the plurality of rollers further comprises:
- a. a first and a second tension ~~eherd~~ cord, wherein each of said first and second tension ~~eherds~~ cords have:
- i. a first relaxed length less than the length of the elongate body;
 - ii. a second stretched length less than the length of the elongate body;
 - iii. a first end fixed to which is an eye ring, wherein said first tension ~~eherd~~ cord eye ring is engaged in a sliding relationship with the first semi circular pivot hoop and wherein said second tension ~~eherd~~ cord eye ring is engaged in a sliding relationship with the second semi circular pivot hoop;
 - iv. a second end fixed to which is a clip, wherein said first tension ~~eherd~~ cord clip is adapted for releasable engagement with the second semi circular hoop and wherein said second tension ~~eherd~~ cord clip is adapted for releasable engagement with the first semi circular hoop;

Appn. Number 10/705,840 Guyon et al.
Amendment dated Thursday, 04/13/2006
Reply to Office Action dated 01/24/2006
Amended 07/26/2006
Reply to Office Action dated 07/07/2006

GAU 3618

so that when the first and second clips are engaged with their respective first and second semi-circular hoops, the first and second tension ~~chord~~ cord assume their second stretched lengths.

14. (Currently Amended). The in line skate guard as claimed in claim 13 wherein the first tension ~~chord~~ cord and said second tension cord have identical construction.
15. (Original). The in line skate as claimed in claim 14 wherein the first and the second semi circular pivot hoops are fabricated from piano wire.
16. (Original). An in line skate guard for an in line skate, said in line skate guard adapted to permit the wearer to walk on a walking surface using a natural human walking gait cycle, said natural human walking gait cycle comprising a heel strike phase, a transition phase from the heel strike phase to a foot flat phase, a foot flat phase, a transition phase between the foot flat phase and the heel off phase, a heel off phase and a toe off phase, said in line skate guard comprising an elongate body having a bottom surface, said bottom surface comprising a plurality of integral contact planes in a serial and contiguous relationship, said contact planes including:
 - a. a first contact plane adapted to contact said walking surface during said heel strike phase;
 - b. a second contact plane adapted to contact the walking surface during said transition phase between the foot flat phase and the heel off phase;
 - c. a third contact plane adapted to contact the walking surface during said foot flat phase;

Appn. Number 10/705,840 Guyon et al.
Amendment dated Thursday, 04/13/2006
Reply to Office Action dated 01/24/2006
Amended 07/26/2006
Reply to Office Action dated 07/07/2006

GAU 3618

- d. a fourth contact plane adapted to contact the walking surface during the transition phase between the foot flat phase and the toe off phase; and,
 - e. a fifth contact surface adapted to contact the walking surface during the toe off phase.
17. (Original). The in line skate guard as claimed in claim 16 wherein:
- a. said first contact plane is raised approximately 45 degrees from the horizontal; and, wherein,
 - b. said fifth contact plane is raised approximately 45 degrees from the horizontal.
18. (Cancelled).